

WALLY
≡

w a l l y t e n d e r 4 3 X




**PETREL GLOBAL SHIPS
& BOATS TRADING LLC**

Office 621, 6th Floor Block A, Business Village.
Port-Saeed Deira, Dubai UAE
www.petrel-global.com, tel.: +971 52 821 6411



Wally shows its sportive side with wallytender43X





Pure, simple,
fast, stylish

and magnificently
seaworthy

- High-speed sheltered passenger and driver experience
- Smooth ride with deep V hull and automated interceptors
- Wave piercing vertical bow
- Full-carbon single molded dashboard
- Wally distinguished driving wheel
- Enhanced visibility
- User-friendly joy-stick controls for easy manoeuvring
- Only two strut extra-large carbon T-top



Sailing hallmark

The wallytender43 draws on Wally's sailing heritage through the laminated sail mounted across the T-top's carbon fiber superstructure. This brand's signature solves the problem of simultaneously delivering the sensation of open-air living and providing shelter from the sun. Made from laminated sail cloth,

the chic, contemporary "Wally" look of the 9 m² (97 ft²) T-top is highly practical, being lighter to reduce displacement of the vessel, and semi-transparent to allow plenty of light shining on those in the shade underneath. Solar panels can be installed on the T-top and coupled with lithium batteries to considerably extend the generator charge.





Your Tender, your way

As with the inboard model, the wallytender43X offers a modular aft deck configuration to suit a range of purposes. Opt for the large sunpad to provide easy-access storage for watertoys under the comfortable lounging space.

The exclusive uniqueness
Wally has ingeniously positioned the retractable passerelle / swim ladder in the stern next to the three outboards for direct and easy access to the shore and to the water.





Solar energy
Solar panels mounted on the T-top to power battery pack running the gyro stabiliser for silent mode at anchor



Triple Outboards

The wallytender43X's standard propulsion package provides triple 300hp Mercury Verados that top out at 40 knots, or owners can opt for the even faster package that includes triple 450R Mercury Verados for an exhilarating maximum speed of 50 knots.





Cockpit meets walkaround

The jewel in the wallytender43's crown is its unique "center cockpit" layout, which provides the driver and passengers with supreme protection from the elements, especially at top speeds.

Alongside the protective benefits of the sheltered cockpit, thanks to the flanking walkways, you can enjoy convenient and safe access to the bow as well as the large sunpad on the foredeck.







Cruise your

comfort
zone





- Push-button anchor system
- Foredeck sunpad
- Protected open-air galley
- Air conditioned center cockpit
- Opening bulwarks
- Removable shower bar
- Retractable swim ladder/passerelle
- Forward and aft deck awnings
- Gyro stabiliser
- Carbon fold-out table
- Convivial seating
- Teak decking
- Sheltered open-air living
- Wraparound fender
- Deck and underwater LED lighting







The wraparound glass windshield cocoons those onboard from three sides while the T-top offers shelter from above. Remarkably, the cockpit windshield's front section has an angular bend of the single panel of glass, achieved without use of a central strut. This enhances visibility from the wheel station, with the added benefit of advancing the aesthetic of the tender.








Supreme
protection

at any speed









Promoting open air living

Because at the end
of the day, this is the best
way to be Wally





Air-conditioned cabin
Generous bathroom with separate shower



wallytender 43

Main technical specifications



The Technical data, performances, designs and graphic reproductions are purely indicative, are not contractual, shall not constitute in any circumstances whatsoever any contractual offer by the shipyard and refer to Europe an standard models of motor yachts built by the shipyard. The only valid technical reference or description is the specific parameters of each motor yacht cited only on purchase of the same. Therefore the only indications binding on the seller are contained solely in the sale agreement and in the relevant specific manual.

Engines

STD: 2 x VOLVO PENTA D6-380 AQ DPI		
Power at 3500 rpm	279 kW	380 mhp
OPT: 2 x VOLVO PENTA D6-440 AQ DPI		
Power at 3700 rpm*	324 kW	440 mhp

Speed

Maximum speed	36 knots /	40 knots
Cruising speed	30 knots /	32 knots

Range

Maximum speed	300 nm /	280 nm
Cruising speed	320 nm /	320 nm

Main sizes

LOA = length overall (ISO 8666)	13,2 m	43 ft 2 in
LH = length hull (ISO 8666)	13,0 m	42 ft 6 in
LWL = length waterline (full load, standard version)	12,0 m	39 ft 4 in
Maximum beam	4,3 m	14 ft 1 in
Depth under propellers (full load, standard version)	1,2 m	3 ft 9 in
Displacement (light ship, standard version)	9,5 t	20944 lb
Displacement (full load, standard version)	12,5 t	27558 lb
Maximum number of persons on board		12
Design category directive 2013/53/EU		B
Certification modules	B+F	RINA Spa

Technical data

Hull type: warped hull with spray rails and aft deadrise		21°
H = overall height	4,7 m	15 ft 3 in
P = pulpit + transom	0,2 m	0 ft 8 in
Fuel tank capacity	1180 l	312 US gal
Water tanks capacity	200 l	53 US gal

Performance specifications

The performance is estimated at the following conditions:

Standard version displacement	10,3 t	22701 lb
at 1/3 of load, clean hull, 25°C air temperature, good weather conditions, 4 persons on board		
Overloading the yacht by	0,5 t	1102 lb
Top speed decreases of		1 knot

wallytender 43 X

Main technical specifications



The Technical data, performances, designs and graphic reproductions are purely indicative, are not contractual, shall not constitute in any circumstances whatsoever any contractual offer by the shipyard and refer to Europe an standard models of motor yachts built by the shipyard. The only valid technical reference or description is the specific parameters of each motor yacht cited only on purchase of the same. Therefore the only indications binding on the seller are contained solely in the sale agreement and in the relevant specific manual.

Engines

STD: 3 X MERCURY VERADO V8 300	
Power 300 Hp	220 kW at 6000 rpm

OPT: 3 x MERCURY VERADO V8 450R

Power at 450 hp	336 kW at 6400 rpm
-----------------	--------------------

Speed

Maximum speed	40 knots / 50 knots
Cruising speed	30 knots / 32 knots

Range

Maximum speed	230 nm / 180 nm
Cruising speed	300 nm / 300 nm

Main sizes

LOA = length overall (ISO 8666)	13,2 m	43 ft 3 in
LH = length hull (ISO 8666)	12,9 m	42 ft 3 in
LWL = length waterline (full load, standard version)	12 m	39 ft 4 in
Maximum beam	4,3 m	14 ft 1 in
Depth under propellers (full load, standard version)	1,25 m	4 ft 1 in
Displacement (light ship, standard version)	9,0 t	19842 lb
Displacement (full load, standard version)	12,0 t	22046 lb
Maximum number of persons on board		12
Design category directive 2013/53/EU		B
Certification modules	B+F	RINA Spa

Technical data

Hull type: warped hull with spray rails and aft deadrise		21°
H = overall height	4,7 m	15 ft 3 in
P = pulpit + transom	0,3 m	1 ft 8 in
Fuel tank capacity	1750 l	462 US gal
Water tanks capacity	200 l	53 US gal

Performance specifications

The performance is estimated at the following conditions:

Standard version displacement	9,9 t	21771 lb
-------------------------------	-------	----------

at 1/3 of load, clean hull, 25°C air temperature, good weather conditions, 4 persons on board

Overloading the yacht by	0,5 t	1102 lb
Top speed decreases of		1 knot

WALLY




**PETREL GLOBAL SHIPS
& BOATS TRADING LLC**

Office 621, 6th Floor Block A, Business Village,
Port-Saeed Deira, Dubai UAE
www.petrel-global.com, tel.: +971 52 821 6411